GOVERNMENT OF GOA QUALITY CONTROL LABORATORY WATER RESOURCES DFEPARTMENT

Test Report No.: WRD/Q.C./F.6-4/Aggr-T-9925,9926/Lab/223/2021-22

Dated: 04 /12/2021.

Laboratory: Bicholim

Sand -T:5208, Cement-T:1300

Sub Div: V (QC)/WRD/Bicholim Goa.

Sub:-"Re-Strenghthening of collapse bank of nalla in Sy. No. 5 at Nagzarwada Bhoma in V.P. Bhoma Priol Constituency of Ponda Taluka".

Ref to requisition No:-WRD/WDXI/SDIV /F.CF/356/2021-22 Dated: 26/10/2021.

Qty. Received: 1 bags each **Date of Receipt:** 23/11/2021 **Tested on:** 24,25 & 26/11/2021

Ref to Specification: CPWD 2009, Vol. I&IS:4031-4-1968

Sample:Sand,20mm, **O.S. N:-**7118,7119,7125, & 7113/SS **Lab. Sample No.**: 2404 To 2407 **Tested by**: Mrs. S.B.Naik Shirodkar.JE.

12.5mm size aggrt., Sand, Cement

REPORT 01 OF 01

2. 12.5 mm Size Aggregate: Particle size distribution: It is not single sized aggregate of 12.5 mm nominal size. (Qty. respectively) REMARK: After blending 20 mm aggregate with 12.5 mm aggregates at the ratio of 1: satisfying the required criteria for graded aggregate of 20 mm nominal size. 3. Sand: (L.S.No.2406) ii) Silt & Clay by S.A. method :- 5.40% (L.S.No.2406) iii) Fineness Modulus :- 3.71 iv) Grading Zone :- I To be used for To be used for REMARK: The observed results are within the permissible limits of the Coarse Sand. 4. Cement: Ultra Tech Cement 43 grade, bearing IS:269 Ordinary Portland cement, Manuf. date: W M-10, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more standard to the standard to the more standard to the more standard to the more standard to the more standard to the standard to the standard to the more standard to the more standard to the st	Γ	Description of sample	Tested for	Results	Max. /Min. value permissible	Remarks				
REMARK: After blending 20 mm aggregate with 12.5 mm aggregates at the ratio of 1: satisfying the required criteria for graded aggregate of 20 mm nominal size. 3. Sand: (L.S.No.2406) i) Silt & Clay by S.A. method :- 5.40% ii) Silt by sedimentation :- 5.71% iii) Fineness Modulus :- 3.71 iv) Grading Zone :- I To be used for To be used for REMARK: The observed results are within the permissible limits of the Coarse Sand. 4. Cement: Ultra Tech Cement 43 grade, bearing IS:269 Ordinary Portland cement, Manuf. date: W M-10, Year -2021 iv) Final Setting Time : 175 minutes (It should not be more samples of the Coarse Sand) iii) Initial Setting Time : 325 minutes (It should not be more samples of the Coarse Sand)	2	20 mm Size Aggregate:	Particle size distributi	on: It is single sized aggre	egate of 20 mm nominal size. (Qty. r	ep. – m^3)				
satisfying the required criteria for graded aggregate of 20 mm nominal size. 3. Sand: (L.S.No.2406) ii) Silt & Clay by S.A. method :- 5.40% (L.S.No.2406) iii) Silt by sedimentation :- 5.71% iii) Fineness Modulus :- 3.71 iv) Grading Zone :- I To be used for REMARK: The observed results are within the permissible limits of the Coarse Sand. 4. Cement: i) Fineness of Cement : 1.06% (It should not be Ultra Tech Cement 43 grade, bearing IS:269 ii) Consistency of cement : 31.50% (It should be in the neighbor Ordinary Portland cement, iii) Initial Setting Time : 175 minutes (It should not be lemont of the Coarse Sand.) Nanuf. date: W M-10, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more	1	12.5 mm Size Aggregat	e: Particle size distribution	on: It is not single sized a	ggregate of 12.5 mm nominal size. (Qty. 1	$ep m^3$)				
 i) Silt & Clay by S.A. method :- 5.40% (L.S.No.2406) ii) Silt by sedimentation :- 5.71% iii) Fineness Modulus :- 3.71 iv) Grading Zone :- I To be used for REMARK: The observed results are within the permissible limits of the Coarse Sand. Cement: i) Fineness of Cement : 1.06% (It should not be Ultra Tech Cement 43 grade, bearing IS:269 ii) Consistency of cement : 31.50% (It should be in the neighbor Ordinary Portland cement, iii) Initial Setting Time : 175 minutes (It should not be lemont of the Coarse Sand. To be used for (It should not be under the permissible limits of the Coarse Sand. 106% (It should not be under the permissible limits of the Coarse Sand. 21.50% (It should not be under the permissible limits of the Coarse Sand. 22.5 minutes (It should not be under the permissible limits of the Coarse Sand. 23.5 minutes (It should not be under the permissible limits of the Coarse Sand. 23.5 minutes (It should not be under the permissible limits of the Coarse Sand. 23.5 minutes (It should not be under the permissible limits of the Coarse Sand. 	REMARK: After blending 20 mm aggregate with 12.5 mm aggregates at the ratio of 1:1 by weight; it is									
(L.S.No.2406) ii) Silt by sedimentation :- 5.71% iii) Fineness Modulus :- 3.71 iv) Grading Zone :- I To be used for REMARK: The observed results are within the permissible limits of the Coarse Sand. 4. Cement: Ultra Tech Cement 43 grade, bearing IS:269 Ordinary Portland cement, iii) Initial Setting Time : 175 minutes (It should not be lemant.) Manuf. date: W M-10, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more	satisfying the required criteria for graded aggregate of 20 mm nominal size.									
iii) Fineness Modulus :- 3.71 iv) Grading Zone :- I To be used for REMARK: The observed results are within the permissible limits of the Coarse Sand. 4. Cement: Ultra Tech Cement 43 grade, bearing IS:269 Ordinary Portland cement, Ordinary Portland cement, Manuf. date: W M-10, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more	Sand: i) Silt & Clay by S.A. method : - 5.40%									
To be used for REMARK: The observed results are within the permissible limits of the Coarse Sand. 4. Cement: Ultra Tech Cement 43 grade, bearing IS:269 Ordinary Portland cement, Manuf. date: W M-10, Year -2021 iv) Grading Zone :- I To be used for i) Fineness of Cement ii) Consistency of cement iii) Consistency of cement iii) Initial Setting Time iv) Final Setting Time		(L.S.No.2406) ii) Silt by sedimentation : - 5.71%								
To be used for 4. Cement: i) Fineness of Cement : 1.06% (It should not be Ultra Tech Cement 43 grade, bearing IS:269 ii) Consistency of cement : 31.50% (It should be in the neighbor Ordinary Portland cement, iii) Initial Setting Time : 175 minutes (It should not be in the neighbor ordinary Portland cement, iii) Initial Setting Time : 325 minutes (It should not be more than 10, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more than 11, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more than 12, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more than 12, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more than 12, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more than 12, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more than 12, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more than 12, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more than 12, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more than 12, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more than 12, Year -2021 iv) Final Setting Time : 325 minutes (It should not be more than 12, Year -2021 iv)			iii) Fineness M	Iodulus : - 3.71						
4. Cement: Ultra Tech Cement 43 grade, bearing IS:269 Ordinary Portland cement, Manuf. date: W M-10, Year -2021 i) Fineness of Cement : 1.06% (It should not be ii) Consistency of cement : 31.50% (It should be in the neighbor : 175 minutes (It should not be le iv) Final Setting Time : 325 minutes (It should not be more		iv) Grading Zone :- I								
Ultra Tech Cement 43 grade, bearing IS:269 Ordinary Portland cement, Manuf. date: W M-10, Year -2021 ii) Consistency of cement : 31.50% (It should be in the neighbor : 175 minutes (It should not be le iv) Final Setting Time : 325 minutes (It should not be more										
Ordinary Portland cement, iii) Initial Setting Time : 175 minutes (It should not be le iv) Final Setting Time : 325 minutes (It should not be more		Cement:		i) Fineness of Cement	: 1.06% (It should not be	more than 10%)				
Ordinary Portland cement, iii) Initial Setting Time : 175 minutes (It should not be le iv) Final Setting Time : 325 minutes (It should not be more	Į	Ultra Tech Cement 43	grade, bearing IS:269	ii) Consistency of cement	: 31.50% (It should be in the neighbor	orhood of 35%)				
\mathcal{L}				•	· ·	ŕ				
\mathcal{L}	I	Manuf. date: W M	-10, Year -2021	iv) Final Setting Time	: 325 minutes (It should not be mo	ore than 600 minutes)				
$\nabla W/L = II/II/U$	(CM/L = 7171769	,	,	, ,	,				
Qty. rep. –.										
To be used for C.C 1:2:4 –. REMARK: The observed results are within the permissible limit for Ordinary Port										

Copy to: 1. The Assistant Engineer, SDIV, WDXI, WRD, Ponda–Goa.

- 2. Copy Submitted to The Superintending Engineer, CPO, WRD, Porvorim Goa for kind information.
- 3. Copy Submitted to The Executive Engineer, W.D. XI, WRD, Ravonfond, Navelim Salcete Goa
- 4. Q.C. Lab file 5. Bill File.